

# Transducers



PART	TYPE	RATED VOLTAGE	RESONANT FREQ.	SPL	VOLT. RANGE	CURRENT (mA)	H (mm)	W (mm)	L (mm)	PIN SPACING	FIRING	WASH	MOUNT TYPE
<a href="#">AT-0927-TT-2-R</a>	Electro-Mechanical	3 V-pk	2730 ±500Hz	86 dBA	2 - 4 V-pk	70 mA	4	9	9	4	Top	No	Thru Hole
<a href="#">AT-0927-TT-3-R</a>	Electro-Mechanical	3 V-pk	2730 ±500Hz	86 dBA	2 - 5 V-pk	70 mA	4	9	9	4	N/A	No	N/A
<a href="#">AT-0927-TT-5-R</a>	Electro-Mechanical	1.5 V-pk	2730 ±500Hz	90 dBA	1 - 2 V-pk	90 mA	4.5	9	9	4	Top	No	Thru Hole
<a href="#">AT-0927-TT-6-R</a>	Electro-Mechanical	3 V-pk	2730 ±500Hz	85 dBA	2 - 4 V-pk	80 mA	4.5	9	9	4	Top	No	Thru Hole
<a href="#">AT-1031-TT-R</a>	Electro-Mechanical	1.5 V-pk	3100 ±500Hz	85 dBA	1 - 3 V-pk	80 mA	6.5	9.6	9.6	4	Top	No	Thru Hole
<a href="#">AT-1127-ST-2-R</a>	Electro-Mechanical	3 V-pk	2730 ±500Hz	90 dBA	2 - 4 V-pk	80 mA	4.3	9	10.5	4	Side	No	Thru Hole
<a href="#">AT-1220-TT-10-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±500Hz	85 dBA	1 - 2 V-pk	20 mA	8.5	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TT-11-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±500Hz	80 dBA	1 - 4 V-pk	10 mA	5.5	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TT-2-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±500Hz	75 dBA	1 - 3 V-pk	30 mA	5.5	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TT-3V-2-R</a>	Electro-Mechanical	3 V-pk	2000 ±500Hz	85 dBA	2 - 5 V-pk	80 mA	4	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TT-5-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±100Hz	73 dBA	1 - 3 V-pk	10 mA	5.5	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TT-8-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±500Hz	80 dBA	1 - 2 V-pk	20 mA	8.5	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TT-9-R</a>	Electro-Mechanical	3.5 V-pk	2048 ±500Hz	85 dBA	3 - 5 V-pk	50 mA	8.5	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TT-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±500Hz	82 dBA	1 - 3 V-pk	10 mA	8.5	12	12	6.5	Top	No	Thru Hole
<a href="#">AT-1220-TWT-5V-R</a>	Electro-Mechanical	5 V-pk	2048 ±200Hz	85 dBA	3 - 8 V-pk	45 mA	9.5	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1224-TWT-12V-2-R</a>	Electro-Mechanical	12 V-pk	2400 ±500Hz	85 dBA	8 - 15 V-pk	40 mA	9.5	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1224-TWT-12V-R</a>	Electro-Mechanical	12 V-pk	2400 ±500Hz	85 dBA	6 - 15 V-pk	40 mA	9.5	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1224-TWT-4-R</a>	Electro-Mechanical	12 V-pk	2400 ±500Hz	85 dBA	6 - 15 V-pk	40 mA	9	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1224-TWT-5V-2-R</a>	Electro-Mechanical	5 V-pk	2400 ±500Hz	87 dBA	3 - 7 V-pk	40 mA	9	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1224-TWT-5V-R</a>	Electro-Mechanical	5 V-pk	2400 ±500Hz	85 dBA	3 - 7 V-pk	50 mA	9.5	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1224-TWT-R</a>	Electro-Mechanical	5 V-pk	2400 ±500Hz	85 dBA	3 - 8 V-pk	40 mA	9	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1228-TT-R</a>	Electro-Mechanical	1.5 V-pk	2800 ±500Hz	85 dBA	1 - 1.7 V-pk	40 mA	10	12	12	6.5	Top	Yes	Thru Hole
<a href="#">AT-1348-TF-LW90-R</a>	Piezo	10 Vp-p	4800 ±500Hz	80 dBA	1 - 30 Vp-p	5 mA	2.5	13	13	0	Top	No	Other
<a href="#">AT-1420-ST-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±500Hz	80 dBA	1 - 3 V-pk	70 mA	7.5	12	13.8	6.5	Side	No	Thru Hole
<a href="#">AT-1425-TWT-R</a>	Electro-Mechanical	1.5 V-pk	2500 ±200Hz	85 dBA	1 - 3 V-pk	30 mA	11	14	14	5	Top	Yes	Thru Hole
<a href="#">AT-1436-TWT-R</a>	Piezo	5 Vp-p	3600 ±500Hz	80 dBA	1 - 20 Vp-p	3 mA	6.8	13.8	13.8	7.6	Top	Yes	Thru Hole
<a href="#">AT-1438-TWT-R</a>	Piezo	5 Vp-p	3800 ±500Hz	80 dBA	1 - 20 Vp-p	1 mA	6.8	13.8	13.8	7.6	Top	Yes	Thru Hole
<a href="#">AT-1440-TT-R</a>	Piezo	5 Vp-p	4000 ±500Hz	80 dBA	1 - 20 Vp-p	3 mA	6.8	13.8	13.8	7.6	Top	No	Thru Hole
<a href="#">AT-1620-TWT-12V-R</a>	Electro-Mechanical	12 V-pk	2048 ±500Hz	85 dBA	9 - 15 V-pk	40 mA	14	16	16	7.6	Top	Yes	Thru Hole
<a href="#">AT-1620-TWT-5-R</a>	Electro-Mechanical	6 V-pk	2048 ±500Hz	85 dBA	3 - 12 V-pk	50 mA	14	16	16	7.6	Top	Yes	Thru Hole
<a href="#">AT-1620-TWT-R</a>	Electro-Mechanical	6 V-pk	2048 ±500Hz	85 dBA	4 - 8 V-pk	40 mA	14	16	16	7.6	Top	Yes	Thru Hole
<a href="#">AT-1720-TT-R</a>	Piezo	3 Vp-p	2000 ±500Hz	70 dBA	3 - 25 Vp-p	3 mA	8.6	17	17	10	Top	No	Thru Hole
<a href="#">AT-1740-TT-3-R</a>	Piezo	3 Vp-p	4000 ±500Hz	78 dBA	1 - 30 Vp-p	1 mA	6.7	16.5	16.5	11	Top	No	Thru Hole
<a href="#">AT-1740-TT-R</a>	Piezo	5 Vp-p	4000 ±500Hz	78 dBA	1 - 30 Vp-p	3 mA	7	16.8	16.8	10	Top	No	Thru Hole

Für weitere Informationen bitte auf die entsprechende Artikelnummer klicken

# Transducers



PART	TYPE	RATED VOLTAGE	RESONANT FREQ.	SPL	VOLT. RANGE	CURRENT (mA)	H (mm)	W (mm)	L (mm)	PIN SPACING	FIRING	WASH	MOUNT TYPE
<a href="#">AT-1750-TFL-LW95-R</a>	Piezo	10 Vp-p	5000 ±500Hz	80 dBA	1 - 30 Vp-p	9 mA	4	16.5	16.5	0	Top	No	Other
<a href="#">AT-1810-T-LW50-R</a>	Piezo	1 Vp-p	1000 ± 500Hz	83 dB	1 - 10 Vp-p	3 mA	2	17.7	17.7	0	Top	No	Flush
<a href="#">AT-1820-TWT-1V-R</a>	Electro-Mechanical	1.5 V-pk	2048 ±500Hz	85 dBA	1 - 2 V-pk	40 mA	10.5	14	18	6.5	Top	Yes	Thru Hole
<a href="#">AT-1820-TWT-6V-R</a>	Electro-Mechanical	6 V-pk	2048 ±500Hz	85 dBA	3 - 10 V-pk	40 mA	10.5	14	18	6.5	Top	Yes	Thru Hole
<a href="#">AT-1830-TT-R</a>	Piezo	10 Vp-p	3000 ±500Hz	88 dBA	1 - 30 Vp-p	3.5 mA	9	18	21.5	17.5	Top	No	Thru Hole
<a href="#">AT-2250-T-LW50-R</a>	Piezo	15 Vp-p	5000 ±500Hz	92 dBA	1 - 30 Vp-p	5 mA	4.5	22	22	0	Top	No	Thru Hole
<a href="#">AT-2310-T-LW100-R</a>	Piezo	3 Vp-p	2000 ±500Hz	65 dBA	1 - 12 Vp-p	3 mA	3.2	22.5	22.5	0	Top	No	Flush
<a href="#">AT-2336-TWT-R</a>	Piezo	12 Vp-p	3600 ±500Hz	90 dBA	3 - 18 Vp-p	8 mA	6	22.5	22.5	0	Top	Yes	Thru Hole
<a href="#">AT-2428-TWT-R</a>	Piezo	12 Vp-p	3000 ±500Hz	92 dBA	3 - 28 Vp-p	8 mA	12.2	24	24	0	Top	Yes	Thru Hole
<a href="#">AT-2429-TWT-R</a>	Piezo	12 Vp-p	2900 ±500Hz	90 dBA	2 - 30 Vp-p	8 mA	16	23.8	23.8	15	Top	Yes	Thru Hole
<a href="#">AT-2440-TWT-R</a>	Piezo	3 Vp-p	4000 ±500Hz	80 dBA	1 - 30 Vp-p	1 mA	7.5	24	24	10	Top	Yes	Thru Hole
<a href="#">AT-2460-TF-LW100-R</a>	Piezo	10 Vp-p	6000 ±500Hz	88 dBA	1 - 30 Vp-p	8 mA	4	24	34	0	Top	No	Flange
<a href="#">AT-2460-TWT-R</a>	Piezo	10 Vp-p	6000 ±500Hz	85 dBA	1 - 30 Vp-p	8 mA	4.5	24	24	10	Top	Yes	Thru Hole
<a href="#">AT-2510-TWT-2-R</a>	Electro-Mechanical	12 V-pk	1250 ± 250 Hz	85 dBA	8 - 14 V-pk	55 mA	12.5	25	25	10.2	Top	Yes	Thru Hole
<a href="#">AT-2720-TT-R</a>	Piezo	10 Vp-p	2048 ±500Hz	88 dBA	1 - 30 Vp-p	3.5 mA	9	23	26.5	22.5	Top	No	Thru Hole
<a href="#">AT-2830-TWT-R</a>	Piezo	12 Vp-p	3000 ±500Hz	93 dBA	3 - 28 Vp-p	8 mA	12.7	28.5	28.5	0	Top	Yes	Thru Hole
<a href="#">AT-3045-TF-LW110-R</a>	Piezo	10 Vp-p	4500 ±500Hz	97 dBA	1 - 50 Vp-p	11 mA	5.1	30	44.5	0	Top	No	Flange
<a href="#">AT-3046-TWT-2-R</a>	Piezo	10 Vp-p	4600 ± 500 Hz	85 dBA	1 - 30 Vp-p	10 mA	7.5	30	30	15.24	Top	No	Thru Hole
<a href="#">AT-3237-TF-LW140-R</a>	Piezo	12 Vp-p	3700 ±500Hz	98 dBA	3 - 28 Vp-p	7 mA	13.5	32	44	0	Top	No	Flange
<a href="#">AT-3425-TWT-R</a>	Piezo	12 Vp-p	2500 ±500Hz	85 dBA	3 - 28 Vp-p	7 mA	11.5	33.6	33.6	0	Top	Yes	Thru Hole
<a href="#">AT-4032-TT-R</a>	Piezo	12 Vp-p	3250 ± 500Hz	100 dBA	1 - 60 Vp-p	40 mA	10.5	40	40	18.5	Top	No	Thru Hole
<a href="#">AT-4228-TWT-F-R</a>	Piezo	12 Vp-p	2800 ±500Hz	92 dBA	3 - 28 Vp-p	7 mA	14	42	42	0	Top	Yes	Thru Hole
<a href="#">AT-4230-TF-LW135-R</a>	Piezo	10 Vp-p	3000 ±500Hz	96 dBA	1 - 30 Vp-p	9 mA	16	41.8	60	0	Top	No	Flange
<a href="#">AT-5210-TT-R</a>	Piezo	18 Vp-p	1000 ±200Hz	105 dBA	1 - 60 Vp-p	10 mA	15.4	54.6	54.6	0	Top	No	Thru Hole
<a href="#">SMT-0440-S-R</a>	Electro-Mechanical	3 V-pk	4000 ±500Hz	70 dBA	2 - 4 V-pk	90 mA	2	4	4	0	Side	No	Surface Mount
<a href="#">SMT-0440-T-R</a>	Electro-Mechanical	3 V-pk	4000 ±500Hz	70 dBA	2 - 4 V-pk	90 mA	2	4	4	0	Top	No	Surface Mount
<a href="#">SMT-0540-S-R</a>	Electro-Mechanical	3 V-pk	4000 ±500Hz	78 dBA	2 - 4 V-pk	100 mA	2	5	5	0	Side	No	Surface Mount
<a href="#">SMT-0540-T-2-R</a>	Electro-Mechanical	3 V-pk	4000 ±500Hz	78 dBA	2 - 4 V-pk	100 mA	3	5	5	0	Top	No	Surface Mount
<a href="#">SMT-0540-T-7-R</a>	Electro-Mechanical	3 V-pk	4000 ±500Hz	78 dBA	2 - 4 V-pk	100 mA	2	5	5	0	Top	No	Surface Mount
<a href="#">SMT-0727-S-R</a>	Electro-Mechanical	3.6 V-pk	2700 ±500Hz	85 dBA	2 - 5 V-pk	120 mA	2	7.5	7.5	0	Side	No	Surface Mount
<a href="#">SMT-0820-S-R</a>	Electro-Mechanical	5 V-pk	2000 ±500Hz	85 dBA	4 - 6 V-pk	70 mA	4	8.5	8.5	0	Side	No	Surface Mount
<a href="#">SMT-0821-S-R</a>	Electro-Mechanical	3.6 Vp-p	2100 ± 500Hz	87 dBA	2.5 - 4.5 Vp-p	90 mA	4	8.5	8.5	0	Side	No	Surface Mount
<a href="#">SMT-0821-T-R</a>	Electro-Mechanical	3.6 V-pk	2100 ±500Hz	87 dBA	2 - 5 V-pk	90 mA	4	8.5	8.5	0	Top	No	Surface Mount
<a href="#">SMT-0823-S-R</a>	Electro-Mechanical	5 V-pk	2300 ±500Hz	87 dBA	3 - 7 V-pk	70 mA	4	8.5	8.5	0	Side	No	Surface Mount

Für weitere Informationen bitte auf die entsprechende Artikelnummer klicken

# Transducers



PART	TYPE	RATED VOLTAGE	RESONANT FREQ.	SPL	VOLT. RANGE	CURRENT (mA)	H (mm)	W (mm)	L (mm)	PIN SPACING	FIRING	WASH	MOUNT TYPE
<a href="#">SMT-0824-SW-5V-R</a>	Electro-Mechanical	5 V-pk	2400 ±200Hz	80 dBA	4 - 6 V-pk	80 mA	5.5	8.5	8.5	0	Side	Yes	Surface Mount
<a href="#">SMT-0824-TW-5V-R</a>	Electro-Mechanical	5 V-pk	2400 ±200Hz	80 dBA	3 - 8 V-pk	60 mA	5.5	8.5	8.5	0	Top	Yes	Surface Mount
<a href="#">SMT-0825-S-2-R</a>	Electro-Mechanical	3.6 V-pk	2500 ±500Hz	87 dBA	2.5 - 4.5 V-pk	90 mA	4	8.5	8.5	0	Side	No	Surface Mount
<a href="#">SMT-0825-S-4-R</a>	Electro-Mechanical	3.6 V-pk	2500 ±500Hz	85 dBA	2.5 - 4.5 V-pk	90 mA	3	8.5	8.5	0	Side	No	Surface Mount
<a href="#">SMT-0825-T-2-R</a>	Electro-Mechanical	3.6 V-pk	2700 ±500Hz	85 dBA	2.5 - 4.5 V-pk	90 mA	3	8.5	8.5	0	Top	No	Surface Mount
<a href="#">SMT-0825-T-R</a>	Electro-Mechanical	3.6 V-pk	2500 ±500Hz	87 dBA	2.5 - 4.5 V-pk	90 mA	4	8.5	8.5	0	Top	No	Surface Mount
<a href="#">SMT-0826-S-R</a>	Electro-Mechanical	3.6 V-pk	2630 ±500Hz	90 dBA	2.5 - 4.5 V-pk	90 mA	3	8	8	0	Side	No	Surface Mount
<a href="#">SMT-0827-S-2-R</a>	Electro-Mechanical	3.6 V-pk	2700 ±500Hz	92 dBA	2.5 - 4.5 V-pk	90 mA	4	8.5	8.5	0	Side	No	Surface Mount
<a href="#">SMT-0827-S-9-R</a>	Electro-Mechanical	3.6 V-pk	2700 ±500Hz	85 dBA	2.5 - 4.5 V-pk	100 mA	2.5	7.5	7.5	0	Side	No	Surface Mount
<a href="#">SMT-0827-SW-3V-R</a>	Electro-Mechanical	3.6 V-pk	2730 ±200Hz	85 dBA	2.5 - 4.5 V-pk	60 mA	5.5	8.5	8.5	0	Side	Yes	Surface Mount
<a href="#">SMT-0827-SW-5V-R</a>	Electro-Mechanical	5 V-pk	2730 ±200Hz	85 dBA	4 - 6 V-pk	80 mA	5.5	8.5	8.5	0	Side	Yes	Surface Mount
<a href="#">SMT-0827-TW-5V-R</a>	Electro-Mechanical	5 V-pk	2730 ±200Hz	85 dBA	3 - 8 V-pk	60 mA	5.5	8.5	8.5	0	Top	Yes	Surface Mount
<a href="#">SMT-0927-S-11-R</a>	Electro-Mechanical	3.6 Vp-p	2730 ± 500 Hz	85 dBA	2 - 4 Vp-p	100 mA	3	8.5	8.5	6	Side	No	Surface Mount
<a href="#">SMT-0927-S-12-R</a>	Electro-Mechanical	5 V-pk	2730 ± 500Hz	85 dBA	3 - 7 V-pk	80 mA	4	9	9	4	Side	No	Surface Mount
<a href="#">SMT-0927-S-8-R</a>	Electro-Mechanical	3.6 V-pk	2700 ±500Hz	87 dBA	2.5 - 4.5 V-pk	100 mA	4	8.5	8.5	0	Side	No	Surface Mount
<a href="#">SMT-0927-T-2-R</a>	Electro-Mechanical	3 V-pk	2730 ±200Hz	85 dBA	2 - 4 V-pk	80 mA	4.5	9	9	0	Top	No	Surface Mount
<a href="#">SMT-0931-S-R</a>	Electro-Mechanical	3.6 V-pk	3100 ±500Hz	89 dBA	3 - 5 V-pk	95 mA	3.2	8.5	8.5	0	Side	No	Surface Mount
<a href="#">SMT-0940-T-3V-R</a>	Piezo	3 Vp-p	4000 ± 500Hz	70 dBA	1-25 Vp-p	1 mA	1.9	9	9	0	Top	No	Surface Mount
<a href="#">SMT-0952-T-5V-R</a>	Piezo	5 Vp-p	5200 ±500Hz	70 dBA	1-25 Vp-p	3 mA	1.9	9	9	0	Top	No	Surface Mount
<a href="#">SMT-1027-S-3-R</a>	Electro-Mechanical	3.6 V-pk	2700 ±500Hz	85 dBA	2.5 - 4.5 V-pk	80 mA	3	10	10	0	Side	No	Surface Mount
<a href="#">SMT-1028-S-2-R</a>	Electro-Mechanical	3.6 v-pk	2830 ±500Hz	93 dBA	3 - 4.6 V-pk	100 mA	3.5	10	10	0	Side	No	Surface Mount
<a href="#">SMT-1028-S-5V-2-R</a>	Electro-Mechanical	5 Vpk	2830 ± 500 Hz	93 dBA	4 - 6 Vpk	70 mA	3.5	10	10	6.4	Side	No	Surface Mount
<a href="#">SMT-1028-T-2-R</a>	Electro-Mechanical	3.6 V-pk	2830 ±500Hz	90 dBA	3 - 4.6 V-pk	100 mA	3.5	10	10	0	Top	No	Surface Mount
<a href="#">SMT-1127-S-R</a>	Electro-Mechanical	3.6 V-pk	2730 ±500Hz	80 dBA	2.5 - 4.5 V-pk	100 mA	2.6	9	10.5	0	Side	No	Surface Mount
<a href="#">SMT-1141-T-5-R</a>	Piezo	5 Vp-p	4100 ± 500 Hz	73 dBA	1 - 25 Vp-p	2.9 mA	1.7	11	9	15	Top	No	Surface Mount
<a href="#">SMT-1220-TW-R</a>	Electro-Mechanical	3 V-pk	2000 ±200Hz	80 dBA	2 - 5 V-pk	35 mA	9	12	12	0	Top	Yes	Surface Mount
<a href="#">SMT-1324-TW-12V-R</a>	Electro-Mechanical	12 V-pk	2400 ±500Hz	85 dBA	8 - 16 V-pk	40 mA	6.5	12.5	12.5	0	Top	Yes	Surface Mount
<a href="#">SMT-1324-TW-1V-R</a>	Electro-Mechanical	1.5 V-pk	2400 ±500Hz	80 dBA	1 - 3 V-pk	30 mA	6.5	12.5	12.5	0	Top	Yes	Surface Mount
<a href="#">SMT-1324-TW-5V-R</a>	Electro-Mechanical	5 V-pk	2400 ±500Hz	85 dBA	4 - 8 V-pk	40 mA	6.5	12.5	12.5	0	Top	Yes	Surface Mount
<a href="#">SMT-1341-T-2-R</a>	Piezo	5 Vp-p	4100 ±500Hz	75 dBA	1 - 25 Vp-p	5 mA	2.5	13	13	0	Top	No	Surface Mount
<a href="#">SMT-1427-S-2-R</a>	Electro-Mechanical	1.5 V-pk	2700 ±500Hz	85 dBA	1.2 - 1.7 V-pk	80 mA	3	11	14	0	Side	No	Surface Mount
<a href="#">SMT-1427-S-3-R</a>	Electro-Mechanical	3 V-pk	2700 ±500Hz	87 dBA	3 - 4.5 V-pk	90 mA	3	11	14	0	Side	No	Surface Mount
<a href="#">SMT-1427-S-4-R</a>	Electro-Mechanical	5 V-pk	2700 ±500Hz	87 dBA	4 - 7 V-pk	90 mA	3	11	14	0	Side	No	Surface Mount
<a href="#">SMT-1427-S-R</a>	Electro-Mechanical	5 V-pk	2700 ±500Hz	85 dBA	3 - 7 V-pk	80 mA	3.4	11	14.2	0	Side	No	Surface Mount

Für weitere Informationen bitte auf die entsprechende Artikelnummer klicken

# Transducers



PART	TYPE	RATED VOLTAGE	RESONANT FREQ.	SPL	VOLT. RANGE	CURRENT (mA)	H (mm)	W (mm)	L (mm)	PIN SPACING	FIRING	WASH	MOUNT TYPE
<a href="#">SMT-1427-T-R</a>	Electro-Mechanical	5 V-pk	2700 ±500Hz	85 dBA	3 - 7 V-pk	80 mA	3.4	11	14.2	0	Top	No	Surface Mount
<a href="#">SMT-1640-S-2-R</a>	Piezo	5 Vp-p	4000 ±500Hz	75 dBA	1 - 25 Vp-p	3 mA	2.5	16	16	0	Side	No	Surface Mount
<a href="#">SMT-2225-T-R</a>	Piezo	10 Vp-p	2500 ±500Hz	80 dBA	1 - 30 Vp-p	8 mA	5.6	22	22	0	Top	No	Surface Mount
<a href="#">SMT-2240-TW-2-R</a>	Piezo	12 Vp-p	4000 ± 500Hz	90 dBA	1 - 30 Vp-p	5 mA	7.4	22.6	22	14.6	Top	No	Surface Mount
<a href="#">UR-1240K-TT-R</a>	Piezo	30 Vrms	40kHz ± 1kHz	NA	30 Vrms	NA	9	12.8	12.8	8.5	Top	No	Thru Hole
<a href="#">UR-1640K-TT-2-R</a>	Piezo	20 Vrms	40kHz ± 1kHz	NA	20 Vrms	NA	12.2	16.2	16.2	10	Top	No	Thru Hole
<a href="#">UT-1240K-TT-R</a>	Piezo	30 Vrms	40kHz ± 1kHz	115 dB	30 Vrms	NA	9	12.8	12.8	8.5	Top	No	Thru Hole
<a href="#">UT-1640K-TT-2-R</a>	Piezo	20 Vrms	40kHz±1kHz	115 dB	20 Vrms	NA	12.2	16.2	16.2	10	Top	No	Thru Hole
<a href="#">UTR-1440K-TT-R</a>	Piezo	140 Vp-p	40kHz ± 0.70	NA	140 Vp-p	NA	9	14.4	14.4	5	Top	No	Thru Hole

Für weitere Informationen bitte auf die entsprechende Artikelnummer klicken

**VIBRATEC AG**

Bauteile für die Elektronik- und Elektroindustrie

VIBRATEC AG  
Industriestrasse 21  
CH-5507 Mellingen

Telefon +41 56 481 77 77  
Telefax +41 56 481 77 70  
E-Mail [info@vibratec.ch](mailto:info@vibratec.ch)