



Übersicht KJ-Elko's

NP Bi-polar

- -40°C ~ +85°C
- 6.3V ~ 50V
- 0.1 μF ~ 100 μF
- 1000 hours
- Φ4 ~ Φ6.3

Wider temperature
 宽温化

KP Bi-polar with wide temperature

- -55°C ~ +105°C
- 6.3V ~ 50V
- 0.1 μF ~ 47 μF
- 1000 hours
- Φ4 ~ Φ6.3

Bi-polarized ↑ 双极化

SS Standard

- -40°C ~ +85°C
- 4V ~ 100V
- 0.1 μF ~ 6800 μF
- 2000 hours
- Φ4 ~ Φ16

Lower leakage
 低漏电流化

SC Low leakage current

- -40°C ~ +85°C
- 6.3V ~ 50V
- 0.1 μF ~ 220 μF
- 2000 hours
- Φ4 ~ Φ6.3

Wider temperature ↓ 宽温化

HT Wide temperature

- -55°C ~ +105°C
- 4V ~ 100V
- 0.1 μF ~ 6800 μF
- 1000 ~ 2000 hours
- Φ4 ~ Φ16

Longer life
 长寿命化

EL Long life assurance

- -55°C ~ +105°C
- 6.3V ~ 50V
- 0.1 μF ~ 3300 μF
- 2000 ~ 3000 hours
- Φ4 ~ Φ16

Higher reliability for auto
 高可靠化 (汽车用)

KH High reliability

- -40°C ~ +125°C
- 10V ~ 450V
- 3.3 μF ~ 2200 μF
- 1000 ~ 5000 hours
- Φ6.3 ~ Φ16

Lower impedance ↓ 低阻抗化

LZ Low impedance

- -55°C ~ +105°C
- 6.3V ~ 50V
- 1 μF ~ 4700 μF
- 1000 ~ 2000 hours
- Φ4 ~ Φ16

Extra longer ↓ 超长寿命化

KL 5000 hour load life

- -55°C ~ +105°C
- 6.3V ~ 100V
- 0.1 μF ~ 3300 μF
- 3000 ~ 5000 hours
- Φ4 ~ Φ16

Higher voltage
 高电压化

HU Mid-to-high voltage

- -40°C ~ +105°C
- 160V ~ 450V
- 3.3 μF ~ 47 μF
- 5000 hours
- Φ12.5 ~ Φ16

Extra lower ↓ 极低阻抗化

KZ Extra lower impedance

- -55°C ~ +105°C
- 6.3V ~ 50V
- 4.7 μF ~ 4700 μF
- 1000 ~ 3000 hours
- Φ4 ~ Φ16

Longer life
 长寿命化

FZ Extra lower impedance with long life

- -55°C ~ +105°C
- 6.3V ~ 100V
- 3.3 μF ~ 4700 μF
- 2000 ~ 5000 hours
- Φ4 ~ Φ16